

Improve Staff Response Times

Butler II is a simple and quick solution for anyone to request service or assistance.



Boost efficiency and productivity

Communication is key for organizations to stay responsive, productive, and efficient. The Butler II push-button transmitter is easy-to-use and may be affixed to almost any surface. The Butler II allows guests and staff alike the flexibility to request assistance with a simple button press.



Empower Guests

Make it easy for guests to request service. The pushbutton notification devices may be firmly affixed to almost any surface, giving customers the means to notify staff when they need immediate attention.



Improve Staff Responsiveness

The Butler II, push-button notification system broadcasts the exact location where assistance is needed. Staff then receive a silent page and respond immediately with assistance.



Enhance Productivity

Faster communication boosts productivity. Enable staff to complete routine duties yet be notified instantly of special needs by either guests or other staff members.

TAKE THE NEXT STEP, CALL FOR PRICING OR INFO:

1.800.437.4996



HOW IT WORKS

Request

Guests or staff can request staff assistance by pressing the button on the Butler II.

Locate

2

3

Staff will receive an alert on a pager advising them assistance is needed along with the exact location.

Respond

Staff responds immediately, improving response time and productivity.

LRSUS.COM





Alphanumeric Pager

- 200 character, 4-line display
- Adjustable contrast and vibration levels
- Multiple vibe & tone alerts
- Uses 1 AAA battery
- Back lit display
- Dimensions: 2.5" x 1.75" x 0.75"

Coaster Call

- Rechargeable NiHM battery
- MPact shock bumper for drop protection
- Any orientation stack Charging
- Flash, vibe & beep modes
- Dimensions: 4" x 4" x .75"



Star Pager

- 4 LED lights

- No battery doors or holes helps keep liquids and dirt out
- Ultra durable design
- Includes detachable belt clip
- Dimensions: 3" x 2.25" x .75"



Door Bell Switch

- Turns Butler II into wireless door bell
- Includes door bell button, connector wire and backplate with screws for wall mounting



Door Sensor

- Monitor any door or window
- Includes one set of sensors and connector cable
- Sensor Dimensions: 2.5" x 0.5" x 0.5"



- Customized alphanumeric messaging
- Individual or group paging
- 5 Buttons for multiple messages
- USB interface for message customization (optional programming kit required)
- UHF frequency (420 470 MHz)
- Operates on 3 AA Batteries
- 1 user configurable sensor/trigger (can be used to monitor doors and windows or as a wireless door bell)
- Dimensions 1.5"w x 7"h x .875"d

LRSUS.COM

Provided by LRS LONG RANGE SYSTEMS, LLC | LRSUS.COM | 1-800-437-4996





